

Leverandørerklæring i forbindelse med
DGNB byggeri:



Produkt(er)	<table border="1"> <thead> <tr> <th>DB-nr.</th> <th>Varenavn</th> <th>Dimensioner</th> </tr> </thead> <tbody> <tr> <td>2300513</td> <td>AeroSana VisConn 10 liter</td> <td>10 liter spand</td> </tr> <tr> <td>2300514</td> <td>AeroSana VisConn Fibre 5 liter</td> <td>5 liter spand</td> </tr> <tr> <td>2297659</td> <td>AeroSana VisConn 600 ml poser</td> <td>600 ml pose</td> </tr> <tr> <td>2297660</td> <td>AeroSana VisConn Fibre 600 ml poser</td> <td>600 ml pose</td> </tr> </tbody> </table>						DB-nr.	Varenavn	Dimensioner	2300513	AeroSana VisConn 10 liter	10 liter spand	2300514	AeroSana VisConn Fibre 5 liter	5 liter spand	2297659	AeroSana VisConn 600 ml poser	600 ml pose	2297660	AeroSana VisConn Fibre 600 ml poser	600 ml pose
	DB-nr.	Varenavn	Dimensioner																		
	2300513	AeroSana VisConn 10 liter	10 liter spand																		
	2300514	AeroSana VisConn Fibre 5 liter	5 liter spand																		
	2297659	AeroSana VisConn 600 ml poser	600 ml pose																		
2297660	AeroSana VisConn Fibre 600 ml poser	600 ml pose																			
DGNB Manual	DGNB-manual for nybyggeri og omfattende renovering 2020																				
Kriterie og Kvalitetstrin	ENV 1.2, Trin 4.																				
Indikator	13																				
H-sætninger	Kan forårsage allergisk hudreaktion. (H317) EUH210: Sikkerhedsdatablad kan på anmodning rekvireres.																				
Blandinger	Indholdsstof	Index-nr.	CAS/EF-nr.	CLP-klassificering	w/w %	Note															
	1,2-benzisothiazol-3(2H)-on	613-088-00-6	2634-33-5 / 220-120-9	Acute Tox. 4;H302, Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Dam. 1;H318, Aquatic Acute 1;H400, M=1	<0,06	1															
	2-methyl-2H-isothiazol-3-one	-	2682-20-4 / 220-239-6	Acute Tox. 3;H301, H311, Skin Corr. 1;H314, Skin Sens. 1A;H317, Acute Tox. 2;H330, Aquatic Acute 1;H400, M=10, Aquatic Chronic 1;H410, M=1	<0,06	2															
	5-chlor-2-methyl-2H-isothiazol-3-on [EF nr. 247-500-7], blanding (3:1) med 2-methyl-2H-isothiazol-3-on [EF nr. 220-239-6]	613-167-00-5	55965-84-9 / -	Acute Tox. 3;H301, Acute Tox. 2;H310, Skin Corr. 1C;H314, Skin Sens. 1A;H317, Acute Tox. 2;H330, Aquatic Acute 1;H400, M=100, Aquatic Chronic 1;H410, M=100	<0,06	3															
1 = Skin Sens. 1; H317: C ≥ 0,05 %. 2 = Skin Sens. 1;H317: C ≥ 0,0015 %. 3 = Eye Dam. 1;H318: C ≥ 0,6 %, Eye Irrit. 2; H319: 0,06 % ≤ C < 0,6 %, Skin Corr. 1C;H314: C ≥ 0,6 %, Skin Irrit. 2;H315: 0,06 % ≤ C < 0,6 %, Skin Sens. 1A;H317: C ≥ 0,0015 %																					
Indhold	Akryl polymer dispersionsklæber																				
Anvendelse	Spraybar klæbning og lufttætning ved tilslutning af dampspærre																				

Dato	08.09.2022
Kontaktperson	Jens Ravn Sørensen / Products Specialist
Underskrift	